

*The logical continuation of a highly successful system.*

## **LCR-100** **Gyrocompass AHRS**



The LCR-100 is the culmination of more than a decade of Fiber Optic Gyro (FOG) and Micro-electromechanical Systems (MEMS) research and development. Northrop Grumman LITEF establishes this new generation of its Attitude and Heading Reference System (AHRS) family, designed to adapt to your specific needs. Our „Made-Lighter-by-Light“ technology is one of the many advantages the system offers. The weight, volume and power consumption of our FOG AHRS are one-third that of comparable systems fitted with mechanical gyros. Fiber Optic Gyros provide excellent reliability and accuracy since they do not rotate and have no moving parts.

**Gyro Compassing.** The LCR-100 is comprised of a triple axis FOG-Instrument Measuring Unit (IMU) gyro and a triad MEMS accelerometer that is capable of true North self-aligning (gyro compassing), like an Inertial Reference System (IRS). This makes unnecessary a magnetic sensor for heading alignment. The LCR-100 also can be augmented with GNSS data to provide hybrid navigational outputs.

### **Your system for today and tomorrow ...**

The outstanding features of the LCR-100 help reduce your total cost of ownership. These in-

clude: small size, low weight, an unlimited attitude range, high accuracy over its entire operating spectrum and gyro-compassing. The LCR-100 can be operated from a standard single 28 volt DC power source. The system also incorporates extensive BITE and self-test circuitry which provides a go/no go annunciator. To improve unit maintenance the system retains an easy-to-access digital failure history stored in solid-state memory for failure isolation.

### **Reliability, Availability, plus performance**

The LCR-100 offers outstanding reliability that results from its high performance, low-cost fiber optic technology and its low 26 watt power consumption – based on the power consumption of the basic digital version of this unit. The rated MTBF of the LCR-100 with no forced cooling exceeds 15,000 hours.

The LCR-100 is qualified to the latest, most stringent civil helicopter standards, and is currently operating on Search and Rescue and precision landing approaches in difficult rotor wing environments. Northrop Grumman LITEF GmbH set a high technical bar for this product, and proceeded to leap over the requirements.

# LCR-100

## Gyrocompass AHRS

### TECHNICAL DATA LCR-100

SPECIFICATIONS		
• Dimensions	AHRU	278 x 102 x 128 mm
• Weight	AHRU	2.7 kg
• Volume	AHRU	3.6 l
• Power	Primary	28 V DC (nominal)
	Auxiliary	28 V DC
	Load	26 W
• MTBF	AHRU	> 15,000 hours
PERFORMANCE (95 %)		
• Attitude	Static (straight & level)	0.1 deg (max.)
	Dynamic	0.2 deg
• True Heading		1 deg
	hybrid	0.5 deg
• Mag Heading		2 deg
• Alignment Time		3 to 10 min
• Flight Path Angle	With GNSS	0.5 deg
• Drift Angle	With GNSS	1.0 deg
• Position	hybrid	GNSS accuracy
	Free inertial	< 12 nm/hr.
• Velocity	With GNSS	0.5 kts
• Inertial Vertical Speed		30 ft/min
• Angular Rates		0.02 deg/s or 0.5%
• Acceleration		5 mg or 0.5%
• Acceleration Range		± 10 g
INTERFACES		
• ARINC-429		
• Synchro		
• RS-232/422 (Test)		
• Discretes		
• Magnetic Sensor Interface		
CERTIFICATIONS		
• TSO/ETSO: C3d, C4c, C5e, C5f, C6d		
• Software Certification DO-178 B Level A		
• Hardware Certification DO-254 Level A		
• DO-160 E		

For more information,  
please contact:  
**Northrop Grumman LITEF GmbH**  
Commercial Aviation  
Loerracher Str. 18  
79115 Freiburg, Germany  
Phone: +49 761 4901-422  
Fax: +49 761 4901-332  
civilair@ng-litef.de  
www.northropgrumman.litef.com

©Northrop Grumman LITEF GmbH, Freiburg, Germany  
All rights reserved.  
Data subject to change without notice.  
February 2012