



2-Wire Remote Interface Artex Products

The most important thing we build is trust



- Upgrade any existing C91a ELT installation to Artex 406 MHz Technology
- Plugs in between new cockpit remote switch and 406 MHz ELT
- Simplify installation and reduce costs by utilizing existing 2, 3 or 4-wire configurations
- One packlist includes all parts required for installation
- TSO C-126 approved
- Another retrofit solution by Cobham Avionics - Artex Products, proving our commitment to reducing installation costs for aircraft owners

Artex Quality • Artex Technology • Artex Service
The name is changing, but our commitment is not

2-Wire Remote Interface

Technical Specifications



The most important thing we build is trust

Upgrade to Artex 406 MHz Technology

Many of the existing TSO C91a installations with Joliet, Pointer and Narco 121.5 MHz ELTs utilize only 2 wires between the cockpit remote switch and the ELT. Other manufacturers of 121.5 MHz ELTs use 3 or 4 wires. The Artex 2-Wire Remote Interface uses just 2 of the existing wires from the wiring harness to connect the new cockpit remote switch to an Artex 406 MHz ELT for a simplified, cost-efficient upgrade.

Continued Commitment to Reduce Installation Costs

The 2-Wire Remote Interface is a follow-up to the Artex ME406 ACE (Absolute Cost Efficiency) ELT. The ME406 ACE is a retrofit for current ACK or Ameri-King 121.5 MHz ELTs and comes complete with a remote switch and adapters to utilize existing wiring.

Technical Specifications

Weights

2-Wire Remote Switch Interface: 2.07oz (59g)
2-Wire ELT Interface: 2.78oz (79g)
Toggle Switch: .35oz (10g)

Built-in Interface D-Sub

Shell Size: 9
Mounting Option: 4-40 jackscrew
Durability: 1000 Cycle minimum
Dielectric Withstanding Voltage: 1000 VAC minimum for 1 minute
Gender: Receptacle (female)

D-Sub 150-0022

Shell Size: 9
Wire Termination Type: Crimp snap
Dielectric Withstanding Voltage: 1000 VAC minimum for 1 minute
Gender: Plug (male)

Pin Crimp 151-0042

Contact Termination: Crimp
AWG: 22-26
Insertion/Extraction Tool: Tyco 91067-2 or equivalent (20-24 AWG)
Tyco 91285-1 or equivalent (24-28 AWG)
Crimp Hand Tool: Tyco 91525-1 or equivalent
Gender: Pin (male)
Size: 20
Insulation Diameter: 0.04 - 0.050 in (1.01 - 1.27 mm)

Backshell 151-0006

Color: Black
Shell Size: 9
Thumbscrew: 4-40
Thumbscrew Torque: 1.5 to 2.0 in-lb (.7 to .22 Nm)

Toggle Switch 140-3349

Pole & Throw: DPDT
Number of Positions: 2
LED Color: Red
Contact Material Rating: 3A @ 30 VDC
LED Forward Peak Current: 25 mA
LED Continuous Forward Current: 20 mA
LED Forward Voltage: 2.1 Volts
Electrical Life: 25000 operations minimum

Part Number

455-0049

For further information please contact:

ACR / Artex

5757 Ravenswood Road
Fort Lauderdale, FL 33312 USA
Tel: 1-800-432-0227
Fax: 1-954-983-5087